

## ET2 High Efficiency Nozzle 10°- 30°



### Technical Features:

Nozzle characterized by the presence of 8 rear jets at 2 different inclinations: 4 x 10° and 4 x 30°. 10° jets permits to have a considerable thrusting power in order to facilitate the passing through the pipe, 30° rear jets make an efficient washing. It's recommended to use ceramic using dirty or recycled water. Ceramic lifetime is longer than s/steel inserts.

- Material: high quality hardened and polished steel alloy or hardened polished stainless/steel
- Holes nr: 4+4 x rear jets + 1 x front jet
- Jets angle: 10°x 4 jets + 30°x 4 jets
- Max Pressure: 250 bar
- Engraving: it's possible to engrave customer company name or lt/bar

### Application:

- Cleaning of soap, grease, mud, sludge, debris, limestone
- Vertical columns and pipes

**ET2 with S/steel Inserts 10°- 30°**

| Part n.   | Description | Hose connection<br> | Rear jets<br> | Front jet<br> | Dimension ØxL (mm)<br> | Weight (Kg)<br> | Diameter Pipe (mm)<br> |
|-----------|-------------|------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| 15120.01A | ET2         | 1/2"F                                                                                                | 4+4 M4x5                                                                                       | 1 - M4x5                                                                                       | 35x47                                                                                                    | 0,16                                                                                               | 25 - 60                                                                                                   |
| 15120.03A | ET2         | 3/4"F                                                                                                | 4+4 M6x8                                                                                       | 1 - M6x8                                                                                       | 48x58                                                                                                    | 0,60                                                                                               | 60 - 200                                                                                                  |
| 15120.04A | ET2         | 1"F                                                                                                  | 4+4 M6x8                                                                                       | 1 - M8x8                                                                                       | 48x58                                                                                                    | 0,65                                                                                               | 60 - 200                                                                                                  |

For S/Steel nozzles write "I" after each part nr. (ex. 15120.01AI)

**ET2 with Ceramic Inserts 10°- 30°**

| Part n.   | Description | Hose connection<br> | Rear jets<br> | Front jet<br> | Dimension ØxL (mm)<br> | Weight (Kg)<br> | Diameter Pipe (mm)<br> |
|-----------|-------------|--------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| 15120.01C | ET2         | 3/4"F                                                                                                  | 4+4 M6x8                                                                                         | 1 - M6x8                                                                                         | 48x58                                                                                                      | 0,60                                                                                                 | 60 - 200                                                                                                    |
| 15120.01C | ET2         | 1"F                                                                                                    | 4+4 M8x8                                                                                         | 1 - M8x8                                                                                         | 48x58                                                                                                      | 0,65                                                                                                 | 60 - 200                                                                                                    |

For S/Steel nozzles write "I" after each part nr. (ex. 15120.01CI)

