

IT Tubo in PVC/NBR di colore nero rinforzato con spirale in PVC rigido antiurto di colore verde. Grazie alla sua parti-colare formulazione mista a gomma nitrilica, ha un'elevata flessibilità a temperature estreme.

Il suo profilo con spirale legger-mente sporgente, garantisce un facile scorrimento sul terreno e una raccordatura semplice e sicura. Elevata resistenza a **oli minerali e grassi industriali**.

A richiesta, si produce nella versione antistatica con cordicella di rame (Cod. TL 02).

• Aspirazione e mandata di liquidi e acque reflue, è particolarmente indicato per impiego su carri botte, anche a bassissime temperature.

EN PVC/NBR hose reinforced with a green anti-shock rigid PVC spiral. Its particular mixed rubber nitrilic formulation enhances a high flexibility at extreme low temperatures.

Its slightly protruding spiral guarantees an easy dragging on the ground and an easy and safe connection. High resistance to **mineral oils and industrial grease**. AS version with copper wire on request (Cod. TL 02).

• Suction and discharge of liquids and waste water in general; ideal to be used on tank trucks, even at **extremely low temperatures**.

Spirale in PVC rigido antiurto leggermente esposta
Slightly exposed anti-shock rigid PVC spiral

COD. TL 01

Ø mm 40-152



Tubo in PVC-NBR
PVC-NBR hose



SCHEDA TECNICA - TECHNICAL DATA	CODICE	Ø INT.	SPES. MIN.	SPES. MAX.	PESO	P.E.	P.S.	DEPR.	R. CURVATURA	LG. ROTOLO	VOLUME
	CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOLUME
		mm	mm	mm	g/m	bar	bar	m H ₂ O	m ²	m	m ³
	TL010400000000*	40	3,5	4,1	620	3,3	10	9	120	50	0,208
	TL010450000000*	45	3,6	4,4	730	3,3	10	9	130	50	0,232
	TL010520000000*	50,8	3,8	4,7	880	3,3	10	9	145	50	0,260
	TL010630000000*	63,5	3,9	5,4	1220	3,0	9	9	200	50	0,535
	TL010760000000*	76,2	4,0	6,0	1530	2,5	7,5	9	225	50	0,635
	TL010800000000*	80	4,0	6,9	1840	2,5	7,5	9	225	50	0,675
	TL010900000000*	90	4,2	7,2	2150	2,2	6,5	9	270	50	0,752
	TL011020000000*	102	4,8	7,7	2650	2,2	6,5	9	300	30	0,676
	TL011270000000*	127	5,1	7,8	3290	2,0	6	9	400	30	0,821
	TL011520000000*	152,4	6,0	9,0	4690	2,0	6	9	460	30	0,982



ARTICOLI DELLA STESSA SERIE
ITEMS IN THE SAME SERIES



APOLLO SUPERFLEX 2 (cod. SF01) p.71



APOLLO SUPERFLEX (cod. AS 01) p.70

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite.

*Available on request, contact our sales office for more info and quantities.

I dati tecnici riportati sono stati misurati a 23°C e al 50% di umidità.

The technical data here reported have been measured at 23°C with 50% humidity.