

APOLLO SUPERFLEX 2

(Cod. SF)



+50°C

-40°C



Tubo in PVC/NBR di colore nero rinforzato con spirale in PVC rigido antiurto di colore grigio. Grazie alla sua particolare formulazione mista a gomma nitrilica, ha un'elevata flessibilità a temperature estreme. Il suo profilo con spirale leggermente sporgente, garantisce un facile scorrimento sul terreno e un'accordatura semplice e sicura. A richiesta si produce nella versione antistatica con cordicella di rame.

• Ottimo per aspirazione in genere, è particolarmente idoneo per uso su carri botte anche a bassissime temperature.


PVC/NBR hose reinforced with a gray anti-shock rigid PVC spiral. Its particular mixed rubber nitrilic formulation gives it a high flexibility at extreme low temperatures. Its profile with a slightly protruding spiral guarantees an easy dragging on the ground and an easy and safe connection. Antistatic version with copper wire on request.

• Suction and delivery of liquids and industrial water in general; ideal to be used on tank trucks, even at extremely low temperatures.



Spirale in PVC rigido antiurto
Anti-shock rigid PVC spiral

Tubo in PVC/NBR / PVC/NBR hose



Scheda tecnica / Technical data

Codice	Ø Int.	Spess. Min.	Spess. Max	Peso	P.E.	P.S.	Depr.	R. Curvatura	Lg. Rotolo
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m
SF010520000000	50,8/2"	4,4	4,9	970	3,3	10	7	160	50
SF010550000000	55	4,6	5,1	1100	3,3	10	7	160	50
SF010600000000	60	4,8	5,3	1260	3,0	9	7	200	50
SF010630000000	63,5/2.1/2"	4,9	5,5	1380	3,0	9	7	210	50
SF010650000000	65	5,0	5,6	1440	3,0	9	7	210	50
SF010700000000	70/2.3/4"	5,1	5,7	1530	3,0	9	7	225	50
SF010760000000	76,2/3"	5,1	5,8	1670	3,0	9	7	250	50
SF010800000000	80	5,1	6,8	1930	2,5	7,5	7	270	50
SF010900000000	90	5,2	7,0	2220	2,5	7,5	7	300	30
SF011020000000	102/4"	5,9	7,6	2770	2,2	6,5	6	335	30
SF011050000000	105	6,0	7,6	2870	2,2	6,5	6	335	30
SF011100000000	110	6,1	7,6	2990	2,0	6	6	360	30
SF011270000000	127/5"	6,3	7,8	3540	1,8	5,5	6	410	30
SF011520000000	152,4/6"	7,4	9,0	5000	1,5	4,5	6	500	20

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity