

APOLLO SUPERFLEX (Cod. AS)



+50°C
-40°C



Tubo in PVC/NBR di colore nero, rinforzato con spirale in PVC rigido antiurto. Speciale formulazione specifica per climi molto rigidi che lo rende migliore dei prodotti analoghi in PVC comunemente impiegati. Versione antistatica con cordicella di rame disponibile su richiesta.


- Spurghi, aspirazione e mandata di liquidi, impiegato su caribotte.

Black PVC/NBR hose, reinforced with an anti-shock rigid PVC spiral. Special formulation conceived for keeping the flexibility at extreme temperatures, better than similar PVC hoses commonly used. Antistatic version with copper wire available on request.

- *Waste Management: suction and discharge of liquids; usually used on tank trunks.*

Spirale in PVC rigido antiurto
Anti-shock rigid PVC spiral

Tubo in PVC/NBR / PVC/NBR hose



Scheda tecnica / Technical data

Codice	Ø Int.	Spess. Min.	Spess. Max	Peso	P.E.	P.S.	Depr.	R. Curvatura	Lg. Rotolo
Code	Ø Int.	Min wall th.	Max wall th.	Weight	W.P.	B.P.	Vac.	Bending	Coil lgth.
	mm/inch	mm	mm	g/m	[bar]	[bar]	m H ₂ O	mm	m
AS01020000000	20*	3,2	3,6	300	5,0	15	10	80	50
AS01025000000	25	3,4	3,9	400	5,0	15	10	80	50
AS01030000000	30*	3,9	4,3	550	5,0	15	10	100	50
AS01032000000	31,8/1.1/4"	3,9	4,3	580	5,0	15	10	105	50
AS01035000000	35*	3,9	4,4	630	4,3	13	10	115	50
AS01038000000	38,1/1.1/2"	3,9	4,4	680	4,3	13	10	125	50
AS01040000000	40*	3,9	4,4	710	4,0	12	10	130	50
AS01045000000	45*	4,1	4,6	840	4,0	12	10	145	50
AS01050000000	50*	4,3	4,8	960	3,3	10	10	160	50
AS01051500000	51,5*	4,3	4,8	990	3,3	10	10	160	50
AS01052000000	50,8/2"	4,3	4,8	980	3,3	10	10	160	50
AS01055000000	55*	4,4	5,0	1090	3,3	10	9	180	50
AS01057000000	57*	4,4	5,0	1130	3,3	10	9	190	50
AS01060000000	60*	4,5	5,1	1220	3,3	10	9	195	50
AS01063000000	63,5/2.1/2"	4,8	5,4	1380	3,3	10	9	210	50
AS01065000000	65*	4,9	5,6	1460	3,0	9	9	210	50
AS01070000000	70*/2.3/4"	5,0	5,8	1570	3,0	9	9	225	50
AS01075000000	75*	5,0	6,1	1740	3,0	9	9	250	50
AS01076000000	76,2/3"	5,0	6,1	1760	3,0	9	9	250	50
AS01080000000	80*	5,1	6,3	1880	2,7	8	9	260	50
AS01090000000	90*	5,3	6,6	2210	2,5	7,5	9	300	30
AS01100000000	100*	6,1	7,6	2840	2,2	6,5	9	330	30
AS01102000000	102/4"	6,1	7,6	2890	2,2	6,5	9	335	30
AS01105000000	105*	6,1	7,7	3000	2,0	6	9	350	30
AS01110000000	110*	6,1	7,7	3110	2,0	6	9	360	30
AS01120000000	120*	6,3	7,9	3490	1,8	5,5	9	390	30
AS01127000000	127/5"	6,3	7,9	3680	1,8	5,5	9	410	30
AS01130000000	130*	7,0	8,3	4120	1,8	5,5	8	420	30
AS01150000000	151,5*	7,4	8,8	5030	1,5	4,5	8	500	20
AS01152000000	152,4/6"	7,4	8,8	5060	1,5	4,5	8	500	20
AS01160000000	160*	7,9	9,3	5550	1,5	4,5	7	540	20
AS01200000000	200*	11,0	12,3	9750	1,2	3,5	7	700	10
AS01203000000	203,2*/8"	11,0	12,3	9900	1,2	3,5	7	700	10

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity