

PULSOR GRAVITY



CONSTRUCTION & INFRASTRUCTURE

Concrete pump and placement



APPLICATIONS

Lay flat hose for concrete bucket (skip).

For discharge to concrete form.

ADVANTAGES

- ¹ Coil flat for easy storage and handling.
- ¹ Lightweight hose.
- ¹ Excellent resistance to wear, abrasion and weather.
- ¹ Abrasion resistance of tube <100mm³.

TECHNICAL DESCRIPTION

Inner tube: NR/SBR, black, smooth.

Reinforcement: synthetic textile.


Cover: NR/SBR, black, fabric impression.

Temperature range: -30 °C to +90 °C.



TRELLEBORG

PULSOR GRAVITY



 CONSTRUCTION & INFRASTRUCTURE		PULSOR GRAVITY						
ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (1) or min. order m
152.0	4.2	160.4	3	10	1.95	40	5513541	1
203.0	4.5	212.0	3	10	3.8	40	5513542	1
254.0	4.5	263.0	3	10	4.7	40	5513543	1

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

