

# SUPERVRAC AL EC



## BULK MATERIALS HANDLING

Bulk tank truck discharge



### APPLICATIONS

Pneumatic transport of bulk abrasive products for the food industry.

Discharge from road and rail tankers and delivery to storage bins: foodstuffs (sugar, flour, milk powder, cattle feed, etc.) and chemicals (fertilizers, granulates, PVC, dye stuffs, etc.).

### ADVANTAGES

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Conductive tube and cover considerably extend service life especially for transfer at high speeds.
- Thanks to the electrical conductivity level of tube, cover and in between, can be used in any ATEX areas.

### TECHNICAL DESCRIPTION

Inner tube: foodgrade abrasion resistant NBR, white, smooth.

Reinforcement: synthetic textile.

Cover: abrasion and weather resistant NBR/PVC, green, fabric impression.

Temperature range: -30 °C to +80 °C.

Electrical properties: Conductive tube and cover,  $R < 10^8 \Omega/m$ . Transversal conductivity ensured through rubber layers. Built-in wire for a safe conductivity between couplings.



### STANDARD/APPROVAL

EU regulation n° 1935/2004.



FDA regulation 21 CFR 177.2600.



French legislation.



### COMPLEMENTARY INFORMATION


This hose has been checked and approved by INERIS (french notified body) for use in any ATEX areas.

AC AL EC  



TRELLEBORG

⚡ SUPERVRAC AL EC





ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
75.0	9 ±1.25	93.0 ±1.5	7	21	2.77	20	5513061	α
75.0	9 ±1.25	93.0 ±1.5	7	21	2.77	40	5513062	ι
89.0	6 ±1.00	101.0 ±1.5	7	21	2.07	20	5513063	ι
89.0	6 ±1.00	101.0 ±1.5	7	21	2.07	40	5513064	ι
100.0	9 ±1.25	118.0 ±1.5	7	21	3.58	20	5513065	α
100.0	9 ±1.25	118.0 ±1.5	7	21	3.58	40	5513066	ι
110.0	6 ±1.25	122.0 ±1.5	7	21	2.53	20	5513067	ι
110.0	6 ±1.25	122.0 ±1.5	7	21	2.53	40	5513068	ι
125.0	8.5 ±1.25	142.0 ±2	7	21	3.9	20	5513153	120
125.0	8.5 ±1.25	142.0 ±2	7	21	3.9	40	5513154	120

Tolerance on length: ±1% (ISO 1307 Standard).

α Upon availability.

Digital version

