

TRELLVAC Handler HD



Evacuation and material handling hoses



APPLICATIONS

Heavy duty working hose on vacuum cleaning trucks for use at the work site.

ADVANTAGES

- Light and flexible with good wear resistance.
- TRELLVAC Handler HD is a working hose for heavy materials when wear resistance is of highest priority.

TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile, woven fabric with embedded steel helix.

Cover: wear and weather resistant SBR/NR, black, corrugated.

Temperature range: -30°C to +90°C.

Electrical properties: non conductive. The helix can be connected to couplings in both ends. Built-in conductive wire.

COMPLEMENTARY INFORMATION

OD measured on top of corrugation.

<u></u>	MINING & QUARRIES		TRELLVAC F	landler HD					
ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (:) or min. order m
102.0	118.0 ±1.6	5	15	0.9	400	3.1	20	5513135	1
102.0	118.0 ±1.6	5	15	0.9	400	3.1	40	2227830	1
127.0	143.0 ±1.6	5	15	0.9	500	3.8	20	5513136	I
127.0	143.0 ±1.6	5	15	0.9	500	3.8	40	1580400	1
152.0	168.0 ±2.0	5	15	0.9	600	4.55	20	5513137	1
204.0	225.0 ±2.0	1.5	4.5	0.9	800	8.2	12	1869200	1
Tolerance on length: +1% (ISO 1307 Standard)									





