

BOAT SANITARY HOSE



MARINE EQUIPMENT

Boat equipment
Water



APPLICATIONS

Effluent hose for leisure boat toilet systems.

ADVANTAGES

- ¹ Flexible.
- ¹ Kink resistant.
- ¹ Diffusion tight (will not be tainted by odour from the toilet system).


TECHNICAL DESCRIPTION


Inner tube: chlorobutyl, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: EPDM, white, fabric impression.

Temperature range: -30°C to +100°C.



**MARINE EQUIPMENT****BOAT SANITARY HOSE**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (.) or min. order m
16.0	27.0 ±1.0	10	32	0.9	64	0.54	20	59013247	200
16.0	27.0 ±1.0	10	32	0.9	64	0.54	40	59013248	200
20.0	31.0 ±1.0	10	32	0.9	80	0.63	20	59013249	200
20.0	31.0 ±1.0	10	32	0.9	80	0.64	40	59013250	1
25.0	36.0 ±1.0	10	32	0.9	100	0.75	20	59013251	200
25.0	36.0 ±1.0	10	32	0.9	100	0.75	40	59013252	200
32.0	43.0 ±1.0	10	32	0.9	130	0.94	20	59013253	200
32.0	43.0 ±1.0	10	32	0.9	130	0.94	40	59013254	200
38.0	49.0 ±1.0	10	32	0.9	160	1.1	40	59013308	1

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version



WWW.TRELLEBORG.COM/FLUIDHANDLING