

# KLENET



## FOOD & BEVERAGE

Food industry  
Cleaning



### APPLICATIONS

Washdown and cleaning in food processing industries, canneries, dairies, slaughterhouses, etc.

### ADVANTAGES

- Very good resistance to high temperatures.
- Smooth for easy handling with light-coloured, non-marking cover.
- Excellent resistance of the cover compound to animal and vegetable grease.
- Contains no phthalate.

### TECHNICAL DESCRIPTION

Inner tube: food grade quality oil resistant NBR, white, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, blue, smooth.

Temperature range: -20 °C to +95 °C.

### STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.



FDA regulation No. 21 CFR 177.2600.



German legislation: BfR recommendation XXI cat. 3.



French legislation.



All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

### COUPLINGS/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.


### COMPLEMENTARY INFORMATION

Not recommended with washdown guns.

TRELLEBORG

KLENET - 57 - WP 10 BAR

95 °C - Made in France



and embossed: week/year - batch number

**FOOD & BEVERAGE****KLENET**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
13.0 ±0.5	21.4 ±0.7	10	30	80	0.3	20	0060962	1
13.0 ±0.5	21.4 ±0.7	10	30	80	0.3	40	0060961	1
13.0 ±0.5	21.4 ±0.7	10	30	80	0.3	60	0060952	4620
13.0 ±0.5	21.4 ±0.7	10	30	80	0.3	120	0060953	1
16.0 ±0.7	25.0 ±0.8	10	30	95	0.38	20	0060964	1
16.0 ±0.7	25.0 ±0.8	10	30	95	0.38	40	0060963	1
16.0 ±0.7	25.0 ±0.8	10	30	95	0.38	60	0060954	1440
16.0 ±0.7	25.0 ±0.8	10	30	95	0.38	120	0060955	1
19.0 ±0.7	28.4 ±0.8	10	30	115	0.48	20	0060966	1
19.0 ±0.7	28.4 ±0.8	10	30	115	0.48	40	0060965	1
19.0 ±0.7	28.4 ±0.8	10	30	115	0.48	60	0060956	1
25.0 ±1.0	35.0 ±1.1	10	30	155	0.62	20	0060968	1
25.0 ±1.0	35.0 ±1.1	10	30	155	0.62	40	0060967	1
25.0 ±1.0	35.0 ±1.1	10	30	155	0.62	60	0060957	1020

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version

