

ASPIVRAC S



MINING & QUARRIES

Evacuation and material handling
hoses



APPLICATIONS

Industrial vacuum cleaning equipment for recovery of industrial waste (crushed minerals, sand, building site rubble, dust, shavings, etc.). For fixed installations (centralized cleaning systems) or mobile installations (vacuum tankers).

Pneumatic suction or discharge of abrasive powder or granulated products (grains, cereals, cattle feed granules, etc.).

ADVANTAGES

- † Robust and easy to handle.
- † Excellent bending radius.
- † Can be manufactured with cuffed ends.
- † Good cover resistance to abrasion.

TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile cords with embedded steel helix.

Cover: weather resistant NR, black, corrugated.

Temperature range: -30°C to +80°C.

Electrical properties: conductive tube and cover,
R<1MΩm/m.



**MINING & QUARRIES****ASPIVRAC S**

ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
50.0 ±1.5	8 ±1.0	66.0 ±2.0	1.5	4.5	0.8	100	1.91	10	0061603	40
50.0 ±1.5	8 ±1.0	66.0 ±2.0	1.5	4.5	0.8	100	1.91	20	0061604	1
60.0 ±1.5	8 ±1.0	76.0 ±2.0	1.5	4.5	0.8	120	2.46	10	0122616	40
60.0 ±1.5	8 ±1.0	76.0 ±2.0	1.5	4.5	0.8	120	2.46	20	0122624	40
70.0 ±1.5	8 ±1.0	86.0 ±2.0	1.5	4.5	0.8	140	2.81	10	0122651	40
70.0 ±1.5	8 ±1.0	86.0 ±2.0	1.5	4.5	0.8	140	2.81	20	0122699	40
75.0 ±1.5	8 ±1.0	91.0 ±2.0	1.5	4.5	0.8	150	3.02	10	0061605	40
75.0 ±1.5	8 ±1.0	91.0 ±2.0	1.5	4.5	0.8	150	3.02	20	0061606	1
80.0 ±1.5	8 ±1.0	96.0 ±2.0	1.5	4.5	0.8	160	3.16	10	0061607	1
80.0 ±1.5	8 ±1.0	96.0 ±2.0	1.5	4.5	0.8	160	3.16	20	0061608	1
90.0 ±1.5	8 ±1.0	106.0 ±2.0	1.5	4.5	0.8	180	3.46	10	0061609	1
90.0 ±1.5	8 ±1.0	106.0 ±2.0	1.5	4.5	0.8	180	3.46	20	0061610	40
100.0 ±1.5	8 ±1.0	116.0 ±2.0	1.5	4.5	0.8	200	3.8	10	0061611	1
100.0 ±1.5	8 ±1.0	116.0 ±2.0	1.5	4.5	0.8	200	3.8	20	0061612	1
110.0 ±1.5	8 ±1.0	126.0 ±2.0	1.5	4.5	0.8	220	4.15	10	0061613	40
110.0 ±1.5	8 ±1.0	126.0 ±2.0	1.5	4.5	0.8	220	4.15	20	0061614	1
125.0 ±1.5	9 ±1.0	143.0 ±2.0	1.5	4.5	0.8	250	5.28	10	0061615	1
125.0 ±1.5	9 ±1.0	143.0 ±2.0	1.5	4.5	0.8	250	5.28	20	0061616	1
150.0 ±1.5	8.5 ±1.0	167.0 ±2.0	1.5	4.5	0.8	300	6.26	10	0061617	1
150.0 ±1.5	8.5 ±1.0	167.0 ±2.0	1.5	4.5	0.8	300	6.26	20	0061618	1
200.0 ±1.5	13 ±1.5	226.0 ±2.5	1.5	4.5	0.8	400	8.92	10	0061619	1

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version

**TRELLEBORG**WWW.TRELLEBORG.COM/FLUIDHANDLING