

HYDRO'K



GENERAL INDUSTRY

Multipurpose oil



APPLICATIONS

A versatile hose for industrial use.

For diesel oil, mineral oil and grease with aromatic content $\leq 50\%$.

Return hose in hydraulic system and for farming equipment.

Sea water (engine cooling) and aqueous solution.

An allround hose for oil, water, compressed air, grease, etc.

ADVANTAGES

- ¹ A multi-purpose hose to minimize inventory.
- ¹ Ozone, abrasion and oil splash resistant cover.

TECHNICAL DESCRIPTION

Inner tube: oil resistant NBR/PVC, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/SBR, black, smooth.

Temperature range: -25°C to $+100^{\circ}\text{C}$.

COMPLEMENTARY INFORMATION

Length 50m: packed in carton.

 GENERAL INDUSTRY			HYDRO'K							
ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (1) or min. order m
5.0 ±0.4	3.25	11.5 ±0.5	16	48	0.80	30	0.12	20	0060722	∞
5.0 ±0.4	3.25	11.5 ±0.5	16	48	0.80	30	0.12	40	0060723	1
5.0 ±0.4	3.25	11.5 ±0.5	16	48	0.80	30	0.12	80	0060724	∞
5.0 ±0.4	3.25	11.5 ±0.5	16	48	0.80	30	0.12	120	0060725	1
6.0 ±0.4	3.5	13.0 ±0.5	16	48	0.80	35	0.15	20	0060727	∞
6.0 ±0.4	3.5	13.0 ±0.5	16	48	0.80	35	0.15	40	0060728	1
6.0 ±0.4	3.5	13.0 ±0.5	16	48	0.80	35	0.15	80	0060729	1
6.0 ±0.4	3.5	13.0 ±0.5	16	48	0.80	35	0.15	120	0060730	1
8.0 ±0.5	3.5	15.0 ±0.6	16	48	0.80	40	0.18	20	0060732	1
8.0 ±0.5	3.5	15.0 ±0.6	16	48	0.80	40	0.18	40	0060733	1
8.0 ±0.5	3.5	15.0 ±0.6	16	48	0.80	40	0.18	80	0060734	1
8.0 ±0.5	3.5	15.0 ±0.6	16	48	0.80	40	0.18	120	0060735	1
10.0 ±0.5	3.5	17.0 ±0.6	16	48	0.80	45	0.22	20	0060737	1
10.0 ±0.5	3.5	17.0 ±0.6	16	48	0.80	45	0.22	40	0060738	1
10.0 ±0.5	3.5	17.0 ±0.6	16	48	0.80	45	0.22	50	0060703	11400
10.0 ±0.5	3.5	17.0 ±0.6	16	48	0.80	45	0.22	80	0060739	1
10.0 ±0.5	3.5	17.0 ±0.6	16	48	0.80	45	0.22	120	0060740	1
13.0 ±0.6	3.75	20.5 ±0.7	16	48	0.35	50	0.27	20	0060742	1
13.0 ±0.6	3.75	20.5 ±0.7	16	48	0.35	50	0.27	40	0060743	1
13.0 ±0.6	3.75	20.5 ±0.7	16	48	0.35	50	0.27	50	0060704	7350
13.0 ±0.6	3.75	20.5 ±0.7	16	48	0.35	50	0.27	80	0060744	1
13.0 ±0.6	3.75	20.5 ±0.7	16	48	0.35	50	0.27	120	0060745	1
15.0 ±0.7	4	23.0 ±0.8	16	48	0.35	55	0.32	20	0060746	∞
15.0 ±0.7	4	23.0 ±0.8	16	48	0.35	55	0.32	40	0060747	1
15.0 ±0.7	4	23.0 ±0.8	16	48	0.35	55	0.32	80	0060748	1
15.0 ±0.7	4	23.0 ±0.8	16	48	0.35	55	0.32	120	0060749	1
16.0 ±0.7	4	24.0 ±0.8	16	48	0.35	60	0.34	20	0060844	∞
16.0 ±0.7	4	24.0 ±0.8	16	48	0.35	60	0.34	40	0060845	1
16.0 ±0.7	4	24.0 ±0.8	16	48	0.35	60	0.34	80	0060846	1
19.0 ±0.7	4.2	27.4 ±0.8	16	48	0.35	65	0.42	20	0060750	1
19.0 ±0.7	4.2	27.4 ±0.8	16	48	0.35	65	0.42	40	0060751	1
19.0 ±0.7	4.2	27.4 ±0.8	16	48	0.35	65	0.42	80	0060753	1
25.0 ±1.0	5	35.0 ±1.1	16	48	0.35	80	0.68	20	0060755	1
25.0 ±1.0	5	35.0 ±1.1	16	48	0.35	80	0.68	40	0060756	1
25.0 ±1.0	5	35.0 ±1.1	16	48	0.35	80	0.68	80	0060757	1

Tolerance on length: ±1% (ISO 1307 Standard).

∞ Upon availability.

Digital version



WWW.TRELLEBORG.COM/FLUIDHANDLING