

OIL 10 D



OIL & GAS

Oil and petroleum
Discharge applications



APPLICATIONS

Delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%.

Limited use for biofuels. Consult us.

TECHNICAL DESCRIPTION


Inner tube: synthetic NBR rubber, black, smooth.

Reinforcement: synthetic textile.

Cover: synthetic NBR/SBR rubber, black, fabric impression.

Temperature range: -30 °C to +80 °C.

Electrical properties: conductive tube, $R < 10^6 \Omega/m$.



**OIL & GAS****OIL 10 D**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
16.0	26.0 ±1.0	10	30	130	0.45	40	5514101	200
19.0	31.0 ±1.0	10	30	160	0.6	40	5514102	200
25.0	37.0 ±1.0	10	30	200	0.74	40	5514103	200
30.0	41.0 ±1.0	10	30	300	0.78	40	5514104	200
32.0	44.0 ±1.0	10	30	320	0.9	20	5514105	1
32.0	44.0 ±1.0	10	30	320	0.9	40	5514106	1
35.0	46.0 ±1.0	10	30	350	0.89	40	5514107	200
38.0	51.0 ±1.2	10	30	380	1.17	20	5514108	1
38.0	51.0 ±1.2	10	30	380	1.17	40	5514109	1
40.0	54.0 ±1.2	10	30	400	1.34	40	5514110	200
45.0	59.0 ±1.2	10	30	450	1.48	40	5514111	200
51.0	65.0 ±1.2	10	30	510	1.65	20	5514112	1
51.0	65.0 ±1.2	10	30	510	1.65	40	5514113	1
60.0	74.0 ±1.5	10	30	600	1.8	40	5514114	160
63.0	75.0 ±1.5	10	30	630	1.66	40	5514115	160
75.0	90.0 ±1.5	10	30	700	2.44	40	5514116	160
80.0	95.0 ±1.5	10	30	760	2.58	40	5514117	160
90.0	105.0 ±1.5	10	30	800	2.88	40	5514118	160
102.0	115.0 ±1.5	10	30	900	2.82	20	5514119	1
102.0	115.0 ±1.5	10	30	900	2.82	40	5514120	1

Tolerance on length: ±1% (ISO 1307 Standard).

**TRELLEBORG**WWW.TRELLEBORG.COM/FLUIDHANDLING