

OIL 10 S



OIL & GAS

Oil and petroleum

Suction and discharge applications



APPLICATIONS

Suction and delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%.

Limited use for biofuels. Consult us.

TECHNICAL DESCRIPTION


Inner tube: synthetic NBR rubber, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: synthetic NBR/SBR rubber, black, fabric impression.

Temperature range: -30°C to +80°C.

Electrical properties: conductive tube, $R < 10^6 \Omega/m$.



**OIL & GAS****OIL 10 S**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
19.0	31.0 \pm 1.0	10	30	0.9	80	0.72	20	5514121	
19.0	31.0 \pm 1.0	10	30	0.9	80	0.72	40	5514122	
25.0	37.0 \pm 1.0	10	30	0.9	100	0.88	20	5514123	
25.0	37.0 \pm 1.0	10	30	0.9	100	0.88	40	5514124	
32.0	44.0 \pm 1.0	10	30	0.9	130	1.05	20	5514125	
32.0	44.0 \pm 1.0	10	30	0.9	130	1.05	40	5514126	
38.0	51.0 \pm 1.2	10	30	0.9	140	1.3	20	5514127	
38.0	51.0 \pm 1.2	10	30	0.9	140	1.3	40	5514128	
40.0	54.0 \pm 1.2	10	30	0.9	160	1.47	20	5514129	
40.0	54.0 \pm 1.2	10	30	0.9	160	1.47	40	5514130	
45.0	57.0 \pm 1.2	10	30	0.9	160	1.46	40	5514131	200
51.0	64.0 \pm 1.2	10	30	0.9	180	1.73	20	5514132	
51.0	64.0 \pm 1.2	10	30	0.9	180	1.73	40	5514133	
60.0	73.0 \pm 1.5	10	30	0.9	200	2.16	40	5514134	160
63.0	76.0 \pm 1.5	10	30	0.9	220	2.26	20	5514135	
63.0	76.0 \pm 1.5	10	30	0.9	220	2.26	40	5514136	
70.0	85.0 \pm 1.5	10	30	0.9	240	2.97	40	5514137	160
75.0	90.0 \pm 1.5	10	30	0.9	260	3.16	20	5514138	
75.0	90.0 \pm 1.5	10	30	0.9	260	3.16	40	5514139	
80.0	96.0 \pm 1.5	10	30	0.9	280	3.38	40	5514140	160
90.0	106.0 \pm 1.5	10	30	0.9	320	3.76	20	5514141	
90.0	106.0 \pm 1.5	10	30	0.9	320	3.76	40	5514142	
102.0	118.0 \pm 1.5	10	30	0.9	320	4.36	20	5514143	
102.0	118.0 \pm 1.5	10	30	0.9	320	4.36	40	5514144	
152.0	172.0 \pm 1.5	10	30	0.9	360	8.74	20	5514145	
152.0	172.0 \pm 1.5	10	30	0.9	360	8.74	40	5514146	

Tolerance on length: \pm 1% (ISO 1307 Standard).**TRELLEBORG**WWW.TRELLEBORG.COM/FLUIDHANDLING