

# OIL 20 D



## OIL & GAS

Oil and petroleum  
Oil cargo



### APPLICATIONS

Delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%, mainly for oil platforms, marine fueling, storage tanks or other industrial facilities.

Limited use for biofuels. Consult us.

### ADVANTAGES

- | Weather, flame, oil projection, UV and ozone resistant.
- | Up to 60m long.

### TECHNICAL DESCRIPTION

Inner tube: NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: CR, black, fabric impression.

Temperature range: -30 °C to +85 °C.


Electrical properties: crossing antistatic wires and conductive tube,  $R < 10^6 \Omega / \text{lg}$ .

and embossed: TRELLEBORG - OIL 20 D - ND - WP 20 bar -  $\Omega$  - month/year - batch number



**TRELLEBORG**

**OIL 20 D**



**OIL & GAS****OIL 20 D**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX TENSILE STRENGTH kN	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
102.0	118.0 ±1.2	20	60	50	815	3.77	60	59011978	1
127.0	145.0 ±1.2	20	60	90	1015	5.32	60	59011979	1
152.0	172.0 ±1.2	20	60	100	1520	7.12	60	59011980	120
203.0	235.0 ±1.6	20	60	150	2030	15.19	40	59013044	40
254.0	292.0 ±1.6	20	60	250	2540	23.28	20	59013045	20

Tolerance on length: ±1% (ISO 1307 Standard).

**TRELLEBORG**