

OIL 20 S



OIL & GAS

Oil and petroleum
Oil cargo



APPLICATIONS

Suction and delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%, mainly for oil platforms, marine fueling, storage tanks or other industrial facilities.

Limited use for biofuels. Consult us.

ADVANTAGES

- ¹ Weather, flame, oil projection, UV and ozone resistant.
- ¹ Up to 60m long.

TECHNICAL DESCRIPTION

Inner tube: NBR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: CR, black, fabric impression.

Temperature range: -30 °C to +85 °C.


Electrical properties: crossing antistatic wires and conductive tube, $R < 10^6 \Omega / \text{lg}$.

and embossed: TRELLEBORG - OIL 20 S - ND - WP 20 bar - Ω - month/year - batch number



TRELLEBORG

OIL 20 S



 OIL & GAS			OIL 20 S							
ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	MAX TENSILE STRENGTH kN	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (.) or min. order m
19.0	32.0 ±1.2	20	60	0.9	3.5	76	0.79	60	59013072	300
25.0	38.0 ±1.2	20	60	0.9	4.5	100	0.97	60	59013074	300
32.0	46.0 ±1.2	20	60	0.9	5.5	128	1.24	60	59013075	300
38.0	52.0 ±1.2	20	60	0.9	9	152	1.5	60	59013077	300
51.0	65.0 ±1.2	20	60	0.9	12	204	1.97	60	59013078	300
63.0	79.0 ±1.2	20	60	0.9	20	252	2.8	60	59013079	240
76.0	92.0 ±1.2	20	60	0.9	30	304	3.45	60	59013080	240
102.0	122.0 ±1.2	20	60	0.9	45	408	5.85	60	59011981	1
127.0	153.0 ±1.6	20	60	0.9	75	509	9.41	60	59011982	1
152.0	180.0 ±1.6	20	60	0.9	100	760	13.21	60	59011983	120
203.0	237.0 ±1.6	20	60	0.9	150	1200	21.82	40	59013049	40
254.0	300.0 ±2.0	20	60	0.9	250	1500	36.29	12	59013050	12
Tolerance on length: ±1% (ISO 1307 Standard).										