

# PUMPADUKT D



## OIL & GAS

Oil and petroleum

Discharge for road and rail tankers



### APPLICATIONS

Discharge of petroleum products, especially designed for applications on reels.

Road tanker equipment for oil delivery (aromatic content up to 50%).

### ADVANTAGES

- ┆ Hose can be cut to length as required.
- ┆ Cover especially designed for oil, abrasion and weather resistance.
- ┆ Electrical conductivity ensured by the tube compound.
- ┆ In compliance with chemicals industry requirements.
- ┆ Suitable for biofuels up to 60 °C.

### TECHNICAL DESCRIPTION

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant CR, black, fabric impression.

Temperature range: -40 °C to +100 °C.

Electrical properties: conductive tube and cover,  $R < 10^6 \Omega / \text{lg}$ .

### STANDARD/APPROVAL

EN 1761:1999, EN 12115:2021.



### COMPLEMENTARY INFORMATION

ID > 100mm: not included in EN 1761 and EN 12115 but designed, made and tested according to the same specifications required by both standards.



and embossed ID 19-100mm: TRELLEBORG - NBR1 - EN 12115:2021 - EN 1761:1999 - D - ND - WP 16bar -  $\Omega$  - -40 TO +100 °C - quarter/year - batch number

and embossed ID 125-250mm: TRELLEBORG - NBR1 - EN 12115:2021 - EN 1761:1999 - D - ND - WP 12bar -  $\Omega$  - -40 TO +100 °C - quarter/year - batch number

**OIL & GAS****PUMPADUKT D**

ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
19.0 ±0.5	6	31.0 ±1.0	16	64	125	0.6	20	0070687	160
19.0 ±0.5	6	31.0 ±1.0	16	64	125	0.6	40	0070688	160
25.0 ±0.5	6	37.0 ±1.0	16	64	150	0.73	20	0070689	160
25.0 ±0.5	6	37.0 ±1.0	16	64	150	0.73	40	0095761	160
32.0 ±0.5	6	44.0 ±1.0	16	64	175	0.81	20	0060106	160
32.0 ±0.5	6	44.0 ±1.0	16	64	175	0.81	40	0126172	160
38.0 ±0.5	6.5	51.0 ±1.0	16	64	225	1.01	20	0123031	160
38.0 ±0.5	6.5	51.0 ±1.0	16	64	225	1.01	40	0125722	160
40.0 ±0.5	6.5	53.0 ±1.0	16	64	240	1.04	20	0070690	160
40.0 ±0.5	6.5	53.0 ±1.0	16	64	240	1.04	40	0123483	160
50.0 ±0.7	8	66.0 ±1.2	16	64	275	1.82	20	0127277	160
50.0 ±0.7	8	66.0 ±1.2	16	64	275	1.82	40	0124618	160
63.0 ±0.8	8	79.0 ±1.2	16	64	300	2.22	20	0070691	120
63.0 ±0.8	8	79.0 ±1.2	16	64	300	2.22	40	0123133	120
65.0 ±0.8	8	81.0 ±1.2	16	64	320	2.26	20	0070692	120
65.0 ±0.8	8	81.0 ±1.2	16	64	320	2.26	40	0070693	120
75.0 ±0.8	8	91.0 ±1.2	16	64	350	2.58	20	0070694	120
75.0 ±0.8	8	91.0 ±1.2	16	64	350	2.58	40	0125085	120
80.0 ±0.8	8	96.0 ±1.6	16	64	370	2.85	20	0070695	120
80.0 ±0.8	8	96.0 ±1.6	16	64	370	2.85	40	0070696	120
100.0 ±0.8	8	116.0 ±1.6	16	64	450	3.28	20	0125916	120
100.0 ±0.8	8	116.0 ±1.6	16	64	450	3.28	40	0123406	120
125.0 ±1.6	9.75	144.5 ±2.0	12	48	750	5.79	1	5514147	40
150.0 ±1.6	10	170.0 ±2.0	12	48	900	6.82	1	5601160	40
200.0 ±2.0	11.75	223.5 ±2.0	12	48	1400	10.84	1	5601203	40
250.0 ±2.4	11.5	273.0 ±2.5	12	48	1800	11.67	1	5514148	40

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version

**TRELLEBORG**