

PUMPADUKT L



OIL & GAS

Oil and petroleum

Suction and discharge for road and rail tankers



APPLICATIONS

Suction and discharge of petroleum products with aromatics up to 50%.

Equipment of road tank trucks for oil and petrol deliveries and their loading/unloading bays.

ADVANTAGES

- ¹ A highly light weight and flexible hose for easy handling. The corrugated cover allows extreme bendings.

TECHNICAL DESCRIPTION

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: oil and weather resistant CR, black, fabric impression, corrugated.

Temperature range: -40 °C to +100 °C.

Electrical properties: conductive tube, $R < 10^6 \Omega/\text{lg}$.

STANDARD/APPROVAL

EN 1761.



and embossed: TRELLEBORG - PUMPADUKT L - NBR 1 - EN 1761:1999 - SD - ND - WP 10bar - Ω /T - month/year - batch number

 OIL & GAS			PUMPADUKT L							
ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (1) or min. order m
50.0 ±0.6	8	66.0 ±1.2	10	40	0.9	100	2.01	20	5013683	160
50.0 ±0.6	8	66.0 ±1.2	10	40	0.9	100	2.01	40	5013684	160
75.0 ±0.6	8	91.0 ±1.2	10	40	0.9	150	3.18	20	5013518	α
75.0 ±0.6	8	91.0 ±1.2	10	40	0.9	150	3.18	40	5013519	ι
100.0 ±0.6	8	116.0 ±1.6	10	40	0.9	200	3.99	40	5013686	120

Tolerance on length: ±1% (ISO 1307 Standard).

α Upon availability.

Digital version

