

VOLUDEC RED



OIL & GAS

Oil and petroleum
Fuel delivery



APPLICATIONS

For hose reels on road tankers for metered delivery of household and automotive fuel.

ADVANTAGES

- † A light weight, flexible hose, highly resistant to abrasion.
- † Static electricity dissipated by conductive braid.
- † Can be supplied ready fitted with swaged gun-metal couplings, sealing caps, or kink resisting spring wire guards.
- † Hose assemblies are individually tested and can be supplied with a hydrostatic proof test certificate in accordance with the regulation.

TECHNICAL DESCRIPTION

Inner tube: oil and petrol resistant NBR/PVC, black, smooth.

Reinforcement: synthetic textile, braided.

Cover: oil and weather resistant NBR/PVC, red, smooth.

Temperature range: -30°C to +55°C.

Electrical properties: built-in-wire for discharge of static electricity.

STANDARD/APPROVAL

EN 1360:2013 type 1.




COMPLEMENTARY INFORMATION

Fitted lengths upon request.



TRELLEBORG - VOLUDEC - EN 1360:2013 - Type 1 - ND - 16 bar - M - month/year





OIL & GAS

VOLUDEC RED



ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
35.0 ±0.8	6.5	48.0 ±1.0	16	48	110	1.11	50	5602765	∞
35.0 ±0.8	6.5	48.0 ±1.0	16	48	110	1.11	60	5602766	∞
38.0 ±0.8	7.25	52.5 ±1.0	16	48	115	1.39	50	5513199	600
38.0 ±0.8	7.25	52.5 ±1.0	16	48	115	1.39	60	5513200	∞

Tolerance on length: ±1% (ISO 1307 Standard).

∞ Upon availability.

Digital version

