

STEAM 16



OIL & GAS

Steam



APPLICATIONS

High pressure steam hose.

TECHNICAL DESCRIPTION

Inner tube: synthetic EPDM rubber, black, smooth.

Reinforcement: steel braid.

Cover: synthetic EPDM rubber, black, fabric impression.

Temperature range: -30°C to +210°C.


Electrical properties: $R < 1M\Omega/lg$.

STANDARD/APPROVAL


BS 5342:1985 type 2 class A.



13-25mm:



32-51mm:



**OIL & GAS****STEAM 16**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
13.0 ±0.75	24.0 ±1	16	160	150	0.47	40	5513652	1200
16.0 ±0.75	28.0 ±1	16	160	190	0.59	40	5513653	840
19.0 ±0.75	32.0 ±1	16	160	230	0.73	40	5513654	1200
25.0 ±0.75	38.0 ±1	16	160	300	0.93	40	5513655	720
32.0 ±0.75	48.0 ±1	16	160	380	1.44	40	5513656	600
38.0 ±0.75	54.0 ±1.2	16	160	380	1.75	40	5513657	600
51.0 ±0.75	69.0 ±1.4	16	160	500	2.31	40	5513658	400

Tolerance on length: ±1% (ISO 1307 Standard).

