



THÖNI CHAMPION

High-quality and proven hose for construction and industrial environments.
Very lightweight, UV-light and ozone resistant and particularly hardwearing.

STRUCTURE

- weaving made of high tenacity multifilament polyester yarn, circular woven
- ageing and ozone resistant EPDM rubber-lining
- exceptionally good adhesion values thanks to special vulcanizing process

ADVANTAGES

- low wear and abrasion resistant
- highly elastic and smooth
- rot-proof, resistant to low and high temperatures
- UV-light and ozone resistant
- additional protection against mechanical and chemical damage on request

i.D. in inch	Dia. in mm	weight gr/m	WP / TP / BP in bar	article- number
1	25	110	12/24/50	CHW025
1 ¼	32	135	12/24/50	CHW032
1 ½	38	185	12/24/50	CHW038
1 ¾	42/45	200/230	12/24/50	CHW042 CHW045
2	52	230	10/20/40	CHW052
2 ½	63/65	280	10/20/40	CHW063
2 ¾	70	340	10/20/40	CHW070
3	75	385	10/20/40	CHW075
3 ½	90	500	9/18/36	CHW090
4	102/110	560/575	8/12/25	CHW102 CHW110
5	125	600	8/12/25	CHW125
6	150	820	8/12/25	CHW150



color white



optional with thin
PU-coating

Lengths, further diameters and colors on request!