



THÖNI REKORD

The premium product on the fire fighting hose market!

Extremely abrasion resistant, flexible and particularly resistant to mechanical damage thanks to a special weaving developed in-house.

Approved according to ÖNorm F2105, DIN 14811 and other international standards.

STRUCTURE


- special weaving made of high tenacity multifilament polyester yarn, circular woven
- ageing and ozone resistant EPDM rubber-lining
- exceptionally good adhesion values due to special vulcanizing process

ADVANTAGES


- impressively robust and durable against mechanical damage
- highly elastic and smooth
- rot-proof
- excellent resistance to low and high temperatures

| i.D. in inch | Dia. in mm | weight gr/m | WP / TP / BP in bar | article- number |
|-----------------|---------------|----------------|------------------------|--------------------|
| 1 | 25 | 190 | 16/24/60 | REW025 |
| 1 ¾ | 42/45 | 275 | 16/24/60 | REW042 REW045 |
| 2 | 52 | 305 | 16/24/60 | REW052 |
| 2 ½ | 63/65 | 410 | 16/24/60 | REW063 |
| 2 ¾ | 70 | 425 | 16/24/60 | REW070 |
| 3 | 75 | 505 | 16/24/60 | REW075 |
| 4 | 110 | 750 | 12/18/35 | REW110 |


Lengths, further diameters and colors on request!



color white



color neon-yellow



color neon-orange