

STORZ couplings *aluminium forged*

Advantage / benefit:forged version, excellent strength and fracture resistance
rotatable

Material:.....aluminium

Seal:.....NBR black

Operating pressure:.....max. 16 bar

Special note:other dimensions and materials upon request

STORZ fixed couplings with male thread

Male thread in mm	26.44	33.25	41.91	47.80	41.91	47.80
Male thread	G3/4	G1	G1¼	G1½	G1¼	G1½
Lug spacing mm	31	31	31	31	66	66
STORZ size	25-D	25-D	25-D	25-D	52-C	52-C
PU units	1	1	1	1	1	1
Item no.	69.0032	69.0033	69.0034	69.0035	69.0036	69.0037

Male thread in mm	59.61	75.18	75.18	87.88	113.03
Male thread	G2	G2½	G2½	G3	G4
Lug spacing mm	66	66	89	89	133
STORZ size	52-C	52-C	75-B	75-B	110-A
PU units	1	1	1	1	1
Item no.	69.0038	69.0039	69.0040	69.0041	69.0042

STORZ cleats with female thread socket, rotatable

Female thread in mm	57.29	72.86	85.56	110.71
Female thread	G2	G2½	G3	G4
Lug spacing mm	66	89	89	133
STORZ size	52-C	75-B	75-B	110-A
PU units	1	1	1	1
Item no.	69.0043	69.0044	69.0045	69.0046

STORZ cleats with male thread socket, rotatable

Male thread in mm	59.61	75.18	87.88	113.03
Male thread	G2	G2½	G3	G4
Lug spacing mm	66	89	89	133
STORZ size	52-C	75-B	75-B	110-A
PU units	1	1	1	1
Item no.	69.0047	69.0048	69.0049	69.0050

STORZ transition pieces

STORZ size 1	52-C	75-B	110-A	150
STORZ size 2	25-D	52-C	75-B	110-A
PU units	1	1	1	1
Item no.	69.0057	69.0058	69.0059	69.0060

STORZ blind couplings with chain

Lug spacing mm	31	66	89	133	148	160
STORZ size	25-D	52-C	75-B	110-A	125	160
PU units	1	1	1	1	1	1
Item no.	69.0051	69.0052	69.0053	69.0054	69.0055	69.0056



8

