

Vibrating Nozzles



Technical Features:

Vibrant nozzle is characterized by an eccentric central body that produces bracking vibrations that crush sedimented obstructions.

- Material: polished tempered stainless/steel A420
- Holes nr: 3/6 rear + 4 central
- Jets angle: 30° rear jets, 90°+45° central vibrating jets
- Max Pressure: 250 bar
- Engraving: it's possible to engrave customer company name or lt/bar

Application:

- Suitable for removing compact limestone, gravel, soil and concrete

Note:

- In order to extend nozzle life time and achieve the best cleaning result, we recommend to plunge it into a lubricating liquid after each use.
- Do not use in gres pipes.



Vibrating Nozzles with Ceramic Inserts + Cover

Part n.	Description	Hose connection 	Rear Jets 	Rotating Jets 	Dimension ØxL (mm) 	Weight (Kg) 	Diameter Pipe (mm) 
18560.01T	Vibrating Nozzle 90°- 45°D + Cover	1/8"F	-	4 - Holes	16x30	0,03	18 - 60
18560.02T	Vibrating Nozzle 90°- 45°D + Cover	1/4"F	3 - M4x5	4 - M4x5	29x56	0,20	30 - 100
18560.03T	Vibrating Nozzle 90°- 45°D + Cover	3/8"F	3 - M4x5	4 - M4x5	29x56	0,20	30 - 100
18560.04TC	Vibrating Nozzle 90°- 45°D + Cover	3/8"F	3 - M6x6	4 - M6x6	35x77	0,40	50 - 150
18560.05TC	Vibrating Nozzle 90°- 45°D + Cover	1/2"F	3 - M6x6	4 - M6x6	35x77	0,40	50 - 150
18560.06TC	Vibrating Nozzle 90°- 45°D + Cover	1/2"F	3 - M6x8	4 - M6x8	50x100	0,90	100 - 200
18560.07TC	Vibrating Nozzle 90°- 45°D + Cover	3/4"F	3 - M6x8	4 - M6x8	50x100	0,90	100 - 200
18560.08TC	Vibrating Nozzle 90°- 45°D + Cover	1" F	3 - M6x8	4 - M6x8	50x100	0,90	100 - 200
18560.09TC	Vibrating Nozzle 90°- 45°D + Cover	1"F	6 - M8x8	4 - M6/8x8	70x160	2,90	100 - 400
18560.10TC	Vibrating Nozzle 90°- 45°D + Cover	1" 1/4"F	6 - M8x8	4 - M6/8x8	70x160	2,90	100 - 400
18560.11TC	Vibrating Nozzle 90°- 45°D + Cover	1" F	6 - M10x10	4 - M10x10	100x180	7,20	200 - 600
18560.12TC	Vibrating Nozzle 90°- 45°D + Cover	1" 1/4"F	6 - M10x10	4 - M10x10	100x180	7,20	200 - 600

Vibrating Nozzles with Ceramic Inserts + Crest Cover

Part n.	Description	Hose connection 	Rear Jets 	Rotating Jets 	Dimension ØxL (mm) 	Weight (Kg) 	Diameter Pipe (mm) 
18560.02V	Vibrating Nozzle 90°- 45°D + Crest Cover	1/4"F	3 - M4x5	4 - M4x5	29x56	0,20	30 - 100
18560.03V	Vibrating Nozzle 90°- 45°D + Crest Cover	3/8"F	3 - M4x5	4 - M4x5	29x56	0,20	30 - 100
18560.04VC	Vibrating Nozzle 90°- 45°D + Crest Cover	3/8"F	3 - M6x6	4 - M6x6	35x77	0,40	50 - 150
18560.05VC	Vibrating Nozzle 90°- 45°D + Crest Cover	1/2"F	3 - M6x6	4 - M6x6	35x77	0,40	50 - 150
18560.06VC	Vibrating Nozzle 90°- 45°D + Crest Cover	1/2"F	3 - M6x8	4 - M6x8	50x100	0,90	100 - 200
18560.07VC	Vibrating Nozzle 90°- 45°D + Crest Cover	3/4"F	3 - M6x8	4 - M6x8	50x100	0,90	100 - 200
18560.08VC	Vibrating Nozzle 90°- 45°D + Crest Cover	1" F	3 - M6x8	4 - M6x8	50x100	0,90	100 - 200
18560.09VC	Vibrating Nozzle 90°- 45°D + Crest Cover	1"F	6 - M8x8	4 - M6/8x8	70x160	2,90	100 - 400
18560.10VC	Vibrating Nozzle 90°- 45°D + Crest Cover	1" 1/4"F	6 - M8x8	4 - M6/8x8	70x160	2,90	100 - 400
18560.11VC	Vibrating Nozzle 90°- 45°D + Crest Cover	1" F	6 - M10x10	4 - M10x10	100x180	7,20	200 - 600
18560.12VC	Vibrating Nozzle 90°- 45°D + Crest Cover	1" 1/4"F	6 - M10x10	4 - M10x10	100x180	7,20	200 - 600

Sharp Tip

19100.01	Sharp Tip M6 suitable for part ns 18560.04/05 C/V	
19100.02	Sharp Tip M8 suitable for part ns 18560.06/07/08/09/10 C/V	
19100.03	Sharp Tip M10 suitable for part ns 18560.11/12 C/V	

Cos.ma.s snc di Abrescia M. & C.

Via del lavoro, 16 - 33080 Roveredo in Piano (PN) - Italy
 Telefono: +39 0434 922560 - Telefax: +39 0434 590737
 e-mail: info@cosmasitalia.com - www.cosmasitalia.com

