

GEKA® automatic hose reel K25

Advantage / benefit: **automatic roll up and comfortable unwind** of the hose without knotting
 continuous adjustment of the hose;
controlled and safe hose-intake
robust metal mount: 180° rotatable;
 incl. mounting kit (4x dowel, 4x screws und 4x washers)
with anti-drip feature due to plug on function for intake hose;
fully assembled brass push-fit system;
 with useful **hose replace function;**
compact size
including high-quality, robust push-fit system and spray nozzle
made of chromed brass

Operating pressure at +20 °C bar: 8
 Temperature range: +4 °C to +45 °C
 Dimensions LxWxH cm: 56,5 (incl. mount) x 24 x 39,5
 Accessories: GEKA® plus spray nozzle; GEKA® plus hose piece 1/2";
 GEKA® plus hose piece 1/2" with water-stop; GEKA® plus tap plug G3/4,
 25 m hose + 2 m intake hose

Hose size	1/2"
Hose ID mm	12,7
Length approx. m	25
Length approx. m intake hose:	2
Packaging	cardboard box
PU units	1
Item no.	42.8720.9



5

automatic roll-up	continuous adjustment	incl. mounting kit and wall mount	intake hose 2 m	with replaceable hose function
incl. push-fit system made of brass	safe and controlled hose-intake	plug on function for intake hose	180° rotatable	

